MODEL 828 WEDGE BARRIER

ASTM F2656-15 M50/P1 CERTIFIED | 15,000 LBS @ 50 MPH



FEATURES

- ASTM F2656-15 M50 P1 Certification
- Hydraulic
- Shallow Mount Design
- **Emergency Fast Operation**
- Up/Down Limit Switch
- Integral LED Light Kit
- Full System Battery Backup



APPLICATIONS







Military &

Government



Centers

OPTIONS

- Master/Remote Control Panel
- Sump Pump
- Cold Weather Packages
- Traffic Warning Lights
- **Network Controls**
- **Battery Backup**
- Loop Detector



AMERISTARPERIMETER.COM | 866-467-2773

Experience a safer and more open world #9984 | 06/2025

AMERISTAR° **ASSA ABLOY**

MODEL 828 WEDGE BARRIER



BARRIER WIDTH	
10'(*)	
12'	
14'	

(*) 10' wide barrier tested by ASTM F2656-15

SPECIFICATIONS	828-Н	
Actuator	Hydraulic	
User Controls	Push Button & Touch Screen Controls	
System Controls	PLC	
Crash Certified	ASTM F2656 M50-P1 15,000 lbs @ 50 mph	
Deploy Time	TYP 3-6 sec	
Emergency Fast Operation	<2 second (approx)	
Phase Power	208 1PH, 208 3PH, 480 3PH	
Material	Hot Dipped Galvanized Steel	
Finish	Zinc Rich Primer and Enamel Top Coat	
Foundation	Shallow depth 19"	
Barrier Deployed Height	38" at Center Point	
Temperate Rating	-40° to 140° F (-40° to 60° C)	

CONTACT YOUR SALESPERSON TO STRENGTHEN YOUR SECURITY WITH A MODEL 828 WEDGE BARRIER.

